

## Ficha Técnica FREEONEXUS PORTABLE.SOUND.SYSTEM



System type	2-way vented enclosure with HF array
High Frequency Device	3 x 2 in
Low Frequency Device	1 x 6 in
Frequency response (-3 dB)	60 Hz - 18 kHz
Max. SPL	115 dB
Coverage angle (H x V)	120° x 50°
Total peak power	400 W
HF continuous power	50 W class D
LF continuous power	150 W class D
Input Connectors	2 x XLR/TRS Combo (balanced) 1 x 3.5mm Jack Stereo
Output Connectors	1 x 6.35mm Jack (unbalanced) 1 x USB type A Charge port
Input Channels	2x MIC/LINE 1x LINE/BT
Mic/Line Controls	Reverb, Low, High, Level
Stereo in/Bluetooth Controls	Pair, Level
Processing	32bit DSP, 24bit AD/DA
Bluetooth	Protocol 5.0, Audio Streaming

Enclosure material	Polypropylene
Finish	Black Textured
Grille material	Powder coated steel
Handles	1 x top
Mounting Pole	1 x bottom
Dimensions (H x W x D):	320 mm x 240 mm x 290 mm 12.59 in x 9.45 in x 11.42 in
Weight	7.5 kg 16.53 lb
USB charging	1 A max
Power Supply	100 - 240 V~, 50 / 60 Hz
Consumption	150 W
Battery type	Rechargeable Lithium-ion 6000mAh
Battery play time (at medium level)	up to 10 hours
Recharging time	less than 4 hours